

Product Overview

The Stryker M Model 1005 Stretcher can be used as a procedural stretcher, an ER gurney, a PACU stretcher, a bariatric stretcher, and a recovery bed.

The Stryker 1005 M-Series Stretcher with Integrated Patient Scale is in excellent condition and certified to proper operating specifications. Stryker's innovative M-Series sets a new standard for effective treatment and safe transport. Supremely mobile and user-friendly, the M-Series stretchers are perfectly suited for fast-paced and rigorous environments such as the Emergency Department because they help greatly reduce the physical strain on clinicians without sacrificing patient care and comfort.



Stryker M Model 1005 Stretcher

Features

- 700 lb capacity
- Available with either a 25" or 29" patient surface width
- Glideaway™ side rails with integrated push/pull handles
- Dual end brake pedals and dual side foot hydraulics
- Assisted backrest
- Integrated utility tray
- Litter-mounted oxygen bottle holder
- Integrated transfer board
- Power-washable design
- Four-wheel, steel-ring brake system with dual-end activators
- Dual side-mounted foot control hydraulics with uni-lower pedal

Features continued on Next Page

Note: The technical data given in this publication is for general information and is subject to change without notice. Actual configuration on the unit may vary. Contact our sales representatives for a complete list of details.



Seattle Technology
3915 152nd St NE
Marysville, WA 98271
1.800.827.3747
stsurg.com

Features Continued

- Four integrated IV receptacles
- Trend./reverse Trend.
- Pneumatic backrest/stationary foot
- Constant descent hydraulics
- Dual-end brake & steer controls
- Extra 5th wheel for additional steering
- Thermoformed ABS base with extra capacity storage tray
- 26" or 30" (66 cm) wide patient surface with 3" (8 cm) Enhanced Comfort Mattress
- Less than 21" low height

Optional Features

- Push Handles
- IV Pole
- SideBrakes
- Knee Gatch

Specifications

Maximum Weight Capacity:

700 lbs (317.5 kg)

Overall Stretcher Length:

84" ($\pm .5$ ") (213.3 cm)

Specifications Continued

Overall Stretcher Width (siderails raised):

33.5" & 37" ($\pm .5$ ") 85.1 cm & 93.9 cm

Overall Stretcher width (side rails Lowered):

30.25" & 30.75" ($\pm .5$ ") 76.8 cm & 78.1 cm

Minimum/ Maximum Bed Height:

20.75"/34" ($\pm .5$ ") 52.7 cm / 86.4 cm

Fowler Angle:

0° to 90° (± 3 °)

Knee Gatch Angle:

0° to 40° (± 1 °)

Trendelenburg/Reverse Trendelenburg:

+16°/-16° (± 1 °)

Optional Scale System Weight

Operating range:

0 lbs. to the maximum capacity of the stretcher

Specifications continued on Next Page

Note: The technical data given in this publication is for general information and is subject to change without notice. Actual configuration on the unit may vary. Contact our sales representatives for a complete list of details.



Seattle Technology
3915 152nd St NE
Marysville, WA 98271

1.800.827.3747

stsurg.com

Specifications Continued

Optional Scale System Accuracy:

Between 10° Trend. & 10° Reverse Trend.* \pm 2
lbs. of weights below 100 lbs. \pm 2% of weights
above 100 lbs.

Optional Scale System Environmental Requirements for Operation:

60° F – 80° F 0% – 90% Relative Humidity

Note: The technical data given in this publication is for general information and is subject to change without notice. Actual configuration on the unit may vary. Contact our sales representatives for a complete list of details.